# KO-03 **EVERY DAY CARRY SERIES**



使用说明书

感谢您购买我们的产品! www.jetbeamlight.com

- 专为露营、EDC、探险&搜救等户外活动
- 采用Luminus SST-70, 寿命长达50000小时
- 可用一节21700电池驱动,兼容20700/18650电池,最 高可达2400流明亮度,326米射程
- 移动电源功能,提供不时之需
- 强力磁吸式尾盖,实现双手自由
- 颈部侧按开关设计,五种亮度和爆闪功能
- 内置USB Type-C充电接口
- 高效恒流电路,智能温控,最大程度保护使用安全及性
- 带电池电量检测功能, 随时掌握电量状态
- 防反接设计,防止电池反装给电路造成危害
- 侧按开关锁定功能,防止误按
- 双面镀膜防刮光学镜片
- 航空级铝合金制造
- 超耐磨军规三级硬质阳极氧化表面处理
- IPX-8级防水
- 1米抗摔高度
- 尾部倒立功能

## 产品参数

- LED: Luminus SST-70
- · 最大输出: 2400流明 • 反光杯:精密光面反光杯
- 镜片:钢化玻璃
- 筒身材质:航空级铝合金
- 筒身处理:军规三级硬质氧化表面耐磨处理
- 使用电池: 1节21700/1节20700/1节18650电池
- 开关: 侧按开关
- 尺寸: 134.8mmX25.8mmX34.3mm
- · 重量: 123克(不含电池)

#### 选用电池

电池类型	尺寸规格	标称电压	是否可用	
可充电锂离子电池	21700	3.7V	推荐	
可充电锂离子电池	20700	3.7V	可用	
可充电锂离子电池	18650	3.7V	可用	

### 亮度与时间

FL 1 STANDARD	极亮	高亮	中亮	低亮	节能	警闪
31/5	2400流明	1100流明	300流明	65流明	10流明	2400流明
()	3.5小时	4.5小时	8.8小时	37小时	130小时	5.2小时
	326米 (最远射程)					
	26677坎德拉 (最大光强)					
V	1米 (防跌落高度)					
m	IPX-8 (水下2米)					

配件: 备用防水O圈、手绳、抱夹、USB Type-C充电线、 3.6V 5100mAh 21700锂电池




01

以上数据是按照国际电筒测量标准ANSI/NEMA, FL1所述 **ラ測量方法 使用一节 IFTReam 3 6V/5100mAh 21700**锂 电池在实验室内测量所得,不同电池或使用环境可能会对以

## 操作手电

#### 装入电池

- 1. 打开尾盖, 从包装取出手电以及电池
- 2. 电池正极朝向手电头部(LED所在的一端)装入手电
- 3. 旋紧尾盖



# <u>∧</u>警告

02

- 1. 请将电池按照正极朝灯头方向放入, 反装电池电筒将 不能工作.
- 2. 不能将光线直接照射眼睛, 以免对眼睛造成伤害

#### 开/关机

短按开关开机、长按0.5s关机

#### 档位切换

开机状态下,单击开关,档位从极亮档→高亮档→中 亮档→低亮档→节能档→循环的顺序调节亮度.

双击开关开启爆闪,再次单击,关闭爆闪.

#### 电量指示灯

侧按键下藏电量指示灯,开机状态下显示电池剩余电量 绿色指示灯常亮,表示电量充足; 绿色指示灯闪烁,表示电量足; 红色指示灯闪烁,表示电量不足 红色指示灯常亮,表示电量严重不足.

#### 充电功能

本品有Type-C充电接口.最大输入5V2A. 充电中,侧按键下的红色LED指示灯闪烁; 绿色LED指示灯常亮,表示电池充电结束.

#### 放电功能

电路具有移动电源功能,最大输出DC5V 2.4A. 放电时电量指示灯会指示剩余电量状况.

#### 智能温控

手电在极亮档工作下会产生大量的热量,为有效延长 LED寿命及防止外壳温度过高,手电缓慢降低亮度, 维持到人体握感舒适的温度.

### 低压隆档功能

在电池电量低时, 手电主动减档以延长工作时间, 直 到减档到节能档,当电池电量过低时,手电关闭.

在未锁键和关机状态下,长按开关,手电闪烁两次, 进入锁键状态;

在锁键状态下,单击或双击,手电闪烁一次,处于锁 键状态下,长按3S,手电闪烁两次解锁成功.

03

照明档带记忆功能,关闭前是什么档位,再次打开时, 亮度为关闭前的档位; 爆闪档不带记忆功能.

### 保养电筒

- 1. 长时间不用手电时请取出电池
- 2. 保存手电时请远离有火和潮湿环境
- 3. 请每半年使用软布清洁电筒的螺牙, 并使用硅润滑油 润滑螺牙, 另请经常清洁手电的导电接触面/接触点.

JETBEAM®产品拥有售后保固服务. 在购买本产品的 15天内, 如果有任何质量问题均可向经销商要求免费 更换. 在购买本产品的60个月内享受免费保固服务. 在 超过60个月免费保固期后,本产品享有终身有限度保 固服务, 如需要更换重要部件则需要收取成本费用,

本保固规则不适用于以下情况:

- 1. 人为破坏, 拆解, 改装本产品
- 2. 错误操作导致产品损坏(如装反电池等)。
- 3. 电池漏液导致产品损坏.
- 4. 盐水或海水腐蚀导致产品损坏

如需协助, JETBEAM® 敬请消费者首先联系购买产品 的经销商或零售商, 以获得最迅速的售后服务或发邮件 到 info@jetbeamlight.com.

备注: 产品数据如有更新, 敬请以JETBEAM官方网站

★ 仅限国内区域, 跨区销售将不给予保修。

## 深圳市杰特明电子科技有限公司

咨询热线: +86-0755-27523445 销售邮箱: info@jetbeamlight.com

网 址: www.jetbeamlight.com

公司地址: 广东省深圳市龙华新区大浪南路墩背工业区 二栋三楼

邮 编: 518109

RŏHS F©CE 🚨 🗵

04

# KO-03 **EVERY DAY CARRY SERIES**



# Manual

Thank you for choosing our products! www.jetbeamlight.com

## **Features**

- Mainly used for outdoor camping, EDC, adventuring, searching & rescuing etc. Uses one Luminus SST-70 with a lifespan of
- Max output of 2400 lumens and throw distance of
- Magnetic tailcap with stand capability
- Powered by 1\*21700 Li-ion battery, compatible with 1\*20700 or 1\*18650 battery. · Power bank function to provide charging for
- mobile devices in an emergency Side switch, five levels of brightness and strobe
- · Built-in Type-C charging port.
- Digitally regulated circuit and inellligent temperature control system to optimize the performance and maximize LED lifespan.
- Power indicator function to know power level at Reverse polarity protection to protect from improper battery installation.
- The lock mode prevents accidental activation · Toughened ultra- clear mineral glass with ani-
- Constructed from aero grade aluminum alloy.
- HAIII military grade hard-anodized finish. Waterproof rating: IPX-8 (2 meters under water).
- Impact resistance of 1meter

### Specifications

- LED: Luminus SST-70
- Maximum output: 2400 lumens Reflector: coated metal reflector
- Lens: Coated toughened glass
- · Body material: Aero grade aluminum alloy Finish: HA III military grade hard-anodized
- · Battery: 1\*21700/1\*20700/1\*18650 battery · Switch: Side Switch
- Dimensions: 134.8mm (Length)x34.3mm (Head) x25.8mm (Tail)
- · Weight: 123g (Without battery and bracket)

### **Battery for Use**

	Type	Nominal Voltage	Compatibility
Rechargeable Lithium battery	21700	3.7V	Yes(recommended)
Rechargeable Lithium battery	20700	3.7V	Yes
Rechargeable	18650	3.7V	Yes

## **Output & Runtime**

Outpu	ı a ı	umin	110				
FL 1 STANDARD	Turbo	High	Medium	Low	Eco	Strobe	
34.5	2400LM	1100LM	300LM	65LM	10LM	1200LM	
()	3.5h	4.5h	8.8h	37h	130h	5.2h	
	326m						
	26677cd						
N.	1m (Impact Resistance)						
m	IPX-8 (Underwater 2 meter)						

Included for Free: O-ring, lanyard, clip, USB Type-C charging cable, 3.6V 5100mAh 21700 rechargeable Li-ion battery




01

The above data complies with American National Standard Institute ANSI/NEMA FI1 Standard. Data was obtained by using one JETBeam 3.6V 5100mAh rechargeable 21700 battery in lab. Different data may result when using different batteries.

## Operation of flashlight

## Insert the battery

- 1. Open the tail cover and remove the flashlight and
- battery from the package 2. Insert the battery's positive pole towards the head of the flashlight (the end where the LED is
- 3. Tighten the end cap and insert the battery



# **⚠** Warning

02

- 1. Please put the battery in the direction of the positive pole toward the lamp head, and the battery flashlight will not work if it is reversed
- 2. Do not shine light directly on the eyes to avoid damage to the eyes.

#### On/Off

Short press the side switch to turn on , keep pressing the side switch for 0.5 seconds to turn off

# Mode Change

When the light is on, short press the switch can change the brightness mode, cycling by Turbo--High--Mid--Low--Eco.

## Strobe Mode

Double press the side switch will access strobe, press the switch again will return off the strobe.

# Power Indicator

When the light is turned on, The LED beneath the side switch will indicate the battery level Stay in Green, battery powerfully charged: Flash in Green, battery power is enough; Flash in Red , battery power is low: Keep in Red , battery power is extremely low and needs recharging.

Charging Built-in Type-c charging port, Max input 5V 2A.
In the charging process, the red LED under the side switch will flash, the green LED will be constant on when charging is completely done

### **Bettery Charging Function**

The circuit has a power bank function with a maximum output of DC5V 2.4A. The power indicator will indicate the remaining power status

#### Intelligent Temperature Control Prolong the lifespan of LED and light with intelligent temperature control design by stepping down the brightness automatically when light is too hot.

Low Voltage Brightness Adjustment When the battery is low, the flashlight will automatically adjust the brightness level to a lower level to extend working time. The flashlight will be turned off when the battery is too low.

### Memory function

03

The light has a memory function. It will access the last used output setting when turning the light off and back on again. Strobe mode has no memory

Lock and unlock When the light is off and unlocked state, long press the switch, the flashlight flashes twice will enter the lock state: in the lock state, click or double click, the flashlight flashes once means the light is in the lock state. Keep pressing till the flashlight flashes two times

05

05

# unlocked into standby.

Light Maintenance

 Take the battery out for storage if light will not be used for a long time 2.Keep the light away from heat, static electricity, and

high humidity Clean the thread and conductive contact of light with soft cloth. Lubricate the threads every 6 months

Warranty
We provide 60 months (5 years) of warranty period for this product from the date of purchase in case defects caused by material or workmanship with normal use Necessary material and labor cost will be charged after

# Free warranty does not cover any damages or

- This product is disassembled or modified by anyone other than an authorized JETBeam warrants 2. This product is damaged by using the wrong battery
- or incorrect usage. 3. This product is damaged by defective batteries (such

#### as battery leak). 4. Salt water and corrosive damage to the unit.

Service 1.In need of warranty service, please contact your local official JETBeam dealer
2.To contact JETBeam, please refer to below

Email:info@ietbeamlight.com Phone:+86-0755-27523445
For the latest update, please visit

www.jetbeamlight.com

04

330X120mm 128g双铜,单黑双面印刷,风琴折